

Rev.C May.-2026

50V~1000V 1.0A DO-41
General purpose silicon rectifier Reverse Voltage 50 to1000V Forward Current 1.0A DO-41 axial package.

Plated axial lead, Low reverse leakage, High forward surge current capability.

General purpose.



PIN1 Cathode PIN2:Anode







See Marking Instructions.


Parameter	Symbol	Rating							Unit
		1N4001G	1N4002G	1N4003G	1N4004G	1N4005G	1N4006G	1N4007G	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current 0.375"(9.5mm) lead length at $T_A=75^\circ\text{C}$	$I_{F\text{ AV}}$	1.0							A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	30.0							A
Typical Junction Capacitance ¹	C_j	15.0							pF
Typical Thermal Resistance ²⁾	R_{JA}	50.0							/W
Operating and Storage Temperature Range	T_j, T_{stg}	-55~+150							

Note:


- 1) Measured at 1MHz and applied reverse voltage of 4.0V D.C.
- 2) Thermal resistance from junction to ambient at 0.375" (9.5mm)lead length,P.C.B. mounted.

Parameter	Symbol	Test Conditions	Rating							Unit
			1N4001G	1N4002G	1N4003G	1N4004G	1N4005G	1N4006G	1N4007G	
Maximum Instantaneous Forward Voltage	V_F	$I_F=1.0\text{A}$	1.1							V
Maximum DC Reverse Current at Maximum DC Blocking Voltage	I_R	$T_A=25$	5.0							A
		$T_A=125$	50.0							A





1



1N4001


Note:

1N4001 Product Type Code

Marking

Type number	Marking code
1N4001G	1N4001
1N4002G	1N4002
1N4003G	1N4003
1N4004G	1N4004
1N4005G	1N4005
1N4006G	1N4006
1N4007G	1N4007

Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

150 180

60 90sec;
- 2

245±5

5±0.5sec;
- 3

2 10 /sec.
- 1.Preheating:150~180 , Time:60~90sec.

2.Peak Temp.:245±5 , Duration:5±0.5sec.

3. Cooling Speed: 2~10 /sec.

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
DO-41	3,000	1	3,000	10	30,000	7 ×6	262×72×90	425×270×200