

/ Descriptions

SOT-23 PNP Silicon PNP transistor in a SOT-23 Plastic Package.


/ Features

 , 2SC4210
High h_{FE} , complementary pair with 2SC4210.

/ Applications

Audio power amplifier application.

/ Equivalent Circuit



/ Pinning




PIN1 Base PIN 2 Emitter PIN 3 Collector

/ h_{FE} Classifications & Marking


h_{FE} Classifications Symbol	O	Y
h_{FE} Range	100 200	160 320

/ Electrical Characteristic Curve




SOT-23

单位: mm



/ Marking Instructions



H

7

O: h_{FE}


Note:

H: Company Code

7: Product Type Code

O: h_{FE} Classifications Symbol Code

() /



Note:

- | | | | | | |
|---|-------|-----|-----------|--------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | | 5±0.5sec; | | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-23	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

/ Notices