

/ Descriptions

TO-220 NPN Silicon NPN transistor in a TO-220 Plastic Package.

/ Features

2SA1011
Complementary pair with 2SA1011.


/ Applications

100W
High voltage switching, AF power amplifier, 100W output predriver applications.

/ Equivalent Circuit



/ Pinning




PIN1 Base PIN 2 Collector PIN 3 Emitter


/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	D	E
h_{FE} Range	60 120	100 200

/ Electrical Characteristic Curve




/ Package Dimensions



Symbol	Dimensions in mils (mm)		Symbol	Dimensions in mils (mm)	
	Min	Max		Min	Max
A	16.1	16.5	A1	10.2	10.5
B	9.0	9.4	B1	10.2	10.5
C	12.6	13.0	C1	12.6	13.0
a	1.2	1.4	a1	1.2	1.4
b1	1.2	1.4	b1	1.2	1.4
c	1.2	1.4	c1	1.2	1.4

/ Marking Instructions



BR

C2344

D: h_{FE}

Note:


BR: Company Code

C2344: Product Type.

D: h_{FE} Classifications Symbol

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|---|--------------------------------------|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255±5 | | 5±0.5sec; | 2.Peak Temp.:255±5 , Duration:5±0.5sec. | |
| 3 | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. | |

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp.:270±5℃ Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type	Units					Dimension (unit mm ³)		

/ TUBE

Package Type	Units					Dimension (unit mm ³)		

Ou 1.TD 0.w ()Tj ET Q B3367116d>-7.5<046404ca>]77 /TT4 1 Tf 4.015.226.4(e)-6.4()]m)