

/ Descriptions

Silicon NPN transistor in a TO-251 Plastic Package.


/ Features

Low $V_{CE(sat)}$, high current and high f_T , excellent linearity of h_{FE} , fast switching time.


/ Applications

Relay drivers, high-speed inverters, and other general high-current switching applications.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter

/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	Q	R	S	T
h_{FE} Range	70 140	100 200	140 280	200 400


/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	60	V
Collector to Emitter Voltage	V_{CEO}	50	V
Emitter to Base Voltage	V_{EBO}	6	V
Collector Current - Continuous	I_C	5	A
Collector Current – Continuous(Pulse)	I_{CP}	8	A
Collector Power Dissipation	P_C	1.0	W
Collector Power Dissipation	$P_C(T_c=25)$	20	W
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	


/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	V_{CBO}	$I_C=10\mu A$ $I_E=0$	60			V
Collector to Emitter Breakdown Voltage	V_{CBO}	$I_C=1mA$ $R_{BE}=\infty$	50			V
Emitter to Base Breakdown Voltage	V_{EBO}	$I_E=10\mu A$ $I_C=0$	6			V
Collector Cut-Off Current	I_{CBO}	$V_{CB}=40V$ $I_E=0$			1.0	μA
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=4.0V$ $I_C=0$			1.0	μA
DC Current Gain	$h_{FE(1)}$	$V_{CE}=2.0V$ $I_C=0.5A$	70		400	
	$h_{FE(2)}$	$V_{CE}=2.0V$ $I_C=4.0A$	35			
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=3.0A$ $I_B=0.15A$		0.22	0.4	V
Base to Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=3.0A$ $I_B=0.15A$		0.95	1.3	V
Transition Frequency	f_T	$V_{CE}=5.0V$ $I_C=1.0A$		180		MHZ
Collector output capacitance	C_{ob}	$V_{CB}=10V$ $f=1MHz$		40		pF
Turn-On Time	t_{on}	$I_C=10I_{B1}=-10I_{B2}=2.0A$		50		ns
Storage Time	t_{stg}			500		ns
Fall Time	t_f			20		ns

/ Electrical Characteristic Curve




/ Package Dimensions



单位: mm

Dimensions In Millimeters			Dimensions In Millimeters		
Symbol	Min	Max	Symbol	Min	Max
a	0.50	0.75	A	5.10	5.50
b	9.00	9.40	B	5.75	6.25
c	0.65	0.85	C	0.65	0.85
e	0.65	0.85	e1	0.65	0.85

/ Marking Instructions



Note:


BR: Company Code

D1803I: Product Type.

R: h_{FE} Classifications Symbol

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-----|-----|----|---------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255 | 5 | 5 | 0.5sec; | 2.Peak Temp.:255 5 , Duration:5 0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

270 5