


Schottky6210g (k)barr(k)i4(w)er di5(sb11(m)des TJET EMC /P /MCID 69ang (en-


Parameter	Symbol	Rating	Unit
Repetitive Reverse Voltage	V_R	70	V
Average Rectified Forward Current	I_F	70	mA
Repetitive Peak Forward Surge Current	I_{FRM}	70	mA
Non-repetitive Peak Forward Surge Current	I_{FSM}	100	mA
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55~150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage	V_F	$I_F=1mA$			410	mV
		$I_F=10mA$			750	mV
		$I_F=15mA$			1	V
Instantaneous Reverse Current	I_R	$V_R=50V$ $V_R=70V$			0.	


/ Electrical Characteristic Curve



/ Marking Instructions



() /



Note:

- 1

25 150

60 90sec;
- 2

245 5

5 0.5sec;
- 3

2 10

/sec.
- 1.Preheating:25~150

, Time:60~90sec.
- 2.Peak Temp.:245 5

, Duration:5 0.5sec.
3. Cooling Speed: 2~10

/sec.

/ Resistance to Soldering Heat Test Conditions

260 5

10 1 sec.

Temp.:260±5

Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm³)		
						"		

/ Notices