

/ Descriptions

Silicon Diode in a SOT-23 Plastic Package.


/ Features

Small signal diode,HF Product.


/ Applications

Switching speed, general-purpose switching applications, high conductivity.

/ Equivalent Circuit



/ Pinning



PIN: See Equivalent Circuit.

/ Marking

Model	BAV23A	BAV23C	BAV23S
Marking	HT7	HT6	HT5


/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Repetitive Reverse Voltage	V_{RRM}	250	V
Reverse Voltage	V_R	200	V
Working Peak Reverse Voltage	V_{RWM}		
RMS Reverse Voltage	$V_{R(RMS)}$	141	V
Average Rectified Forward Current	I_{FM}	400	mA
Non-repetitive Peak Forward Surge Current	$I_{FSM(1)}$ (pulse width=1.0 μ S)	9.0	A
	$I_{FSM(2)}$ (pulse width=100 μ S)	3.0	A
	$I_{FSM(3)}$ (pulse width=10ms)	1.7	A
Repetitive Peak Forward Surge Current	I_{FRM}	625	mA
Power Dissipation	P_D	350	mW
Thermal Resistance, Junction to Ambient	R	357	/W
Junction and Storage Temperature Range	T_j, T_{stg}	-65 150	


/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Breakdown Voltage	V_R	I_R	250			V
Forward Voltage	V_F	$I_F=100mA$			1.0	V
		$I_F=200mA$			1.25	V
Instantaneous Reverse Current	I_R	$T_J=25$			100	nA
		$T_J=150$			100	
Total Capacitance	C_T	$V_R=0$ $f=1.0MHz$			5.0	pF
Reverse Recovery Time	t_{rr}	$I_F=I_R=30mA$ $I_{RR}=0.1 \times I_R$ $R_L=100$			50	ns

/ Package Dimensions



/ Marking Instructions



Note:

H: Company Code

T7: Product Type Code

() /

Note:

- | | | | |
|---|-----------|-------------|---|
| 1 | 150 ~ 180 | 60 ~ 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245 ~ 5 | 5 ~ 0.5sec; | 2.Peak Temp.:245 ~ 5 , Duration:5 ~ 0.5sec. |
| 3 | 2 ~ 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260 ± 5	10 ± 1 sec.	Temp.:260±5	Time:10±1 sec
---------	-------------	-------------	---------------

/ Packaging SPEC.

/ REEL

Package Type	Units	Dimension	(unit mm ³)
--------------	-------	-----------	-------------------------