

/ Descriptions

BRCO7330HME

CMOS

300mA

30V

CMOS

/ Features

- ◆
 - ◆
 - ◆
 - ◆
 - ◆
 - ◆
 - ◆
 - ◆
 - ◆
- ±


±

μ


/ Applications

- ◆
- ◆
- ◆

/ Typical Application



/ Pinning




/ Absolute Maximum Ratings(Ta=25)

/ Electrical Characteristics(TA=25 , VIN=VOUT+1V, CIN=COUT=1uF, unless otherwise specified)

						V
						V
						uA
						uA
						mA
						mV
						mA
						V
						V
						Ω
						mV
						%/V
						ppm/
						dB




/ Package Dimensions




Dimensions in Millimeters			Dimensions in Millimeters		
Symbol	Min	Max	Symbol	Min	Max
L	2.82	3.02	E1	0.85	1.05
B	1.50	1.70	a	0.35	0.50
C	0.90	1.30	c	0.10	0.20

L1	0.68	0.82	b	0.35	0.55
----	------	------	---	------	------

/ Marking Instructions



7330H

 $\pm$ $\pm$ $\pm$ $\pm$ $\pm$ $\pm$

	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box

6 6