








单位: mm

Dimensions in mm		Symbol		Dimensions in mm		Symbol	
Min	Max			Min	Max		
5.95	6.25			2.20	2.40	B	
2.24	2.34			0.95	1.25	e1	
4.43	4.73			0.50	0.90	e2	
9.45	9.95			0.45	0.55	L1	
1.29	1.78			0.45	0.55	b	
		D	6.45	6.75	L3	0.60	0.90
		D1	5.10	5.50	K	0.00	0.10

TO-252



BR

840


Note:

BR: Company Code

840: Product Type Code

****: Lot No. Code, code change with Lot No

Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

1. 150 180 60 90sec; 1.Preheating:150~180 , Time:60~90sec.
2. 245±5 5±0.5sec; 2.Peak Temp.:245±5 , Duration:5±0.5sec.
3. 2 10 /sec. 3. Cooling Speed: 2~10 /sec.

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
TO-252	2,500	2	5,000	6	30,000	13 ×16	360×360×50	380×335×366

/ TUBE

Package Type	Units					Dimension (unit mm ³)		
	Units/Tube	Tubes/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Tube	Inner Box	Outer Box
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180