

/ Descriptions

Silicon NPN transistor in a TO-92 Plastic Package.


/ Features

Excellent h_{FE} linearity, low noise, complementary pair with KTA1266.

/ Applications

General amplifier and switching application.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter


/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	O	Y	GR	BL
h_{FE} Range	70~140	120~240	200~400	300~700

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	60	V
Collector to Emitter Voltage	V_{CEO}	50	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current - Continuous	I_C	150	mA
Base Current - Continuous	I_B	50	mA
Collector Power Dissipation	P_C	625	mW
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55~150	

Parameter Symbol


/ Electrical Characteristic Curve




/ Package Dimensions

T0-92

Unit: mm



/ Marking Instructions



Note:


BR: Company Code.

C3198: Product Type.

GR: h_{FE} Classifications Symbol

****: Lot No. Code,code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



1

25 150

60 90sec;

Note:
1.Preheating:25~150