


Schottky Barrier Diode in a TO-220F Plastic Package.

Low forward voltage drop, low power losses, High efficiency operation.

For use in high frequency inverters, switching power supplies, freewheeling diodes, OR-ing diode, dc-to-dc converters and reverse battery protection.



PIN1 Anode PIN 2 Cathode PIN 3 Anode



See Marking Instructions.


Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RM} V_{RSM} V_{DC}	150	V
RMS Voltage	V_{RMS}	105	V
Average Rectified Output Current	$I_{F(AV)}$	2×20	A
Non Repetitive Peak Surge Current	I_{FSM}	300	A
Thermal Resistance Junction to Case	$R_{\theta JC}$	4.0	$^{\circ}C/W$
Junction and Storage Temperature Range	T_j T_{stg}	-40 +150	$^{\circ}C$


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Breakdown Voltage	V_{BR}	$I_R=1mA(T_a=25^{\circ}C)$	150			V
Forward Voltage	V_F	$I_F=5A(T_a=25^{\circ}C)$		0.68		V
		$I_F=10A(T_a=25^{\circ}C)$		0.76		V
		$I_F=20A(T_a=25^{\circ}C)$		0.89	1.05	V
		$I_F=5A(T_a=125^{\circ}C)$		0.56		V
		$I_F=10A(T_a=125^{\circ}C)$		0.63		V
		$I_F=20A(T_a=125^{\circ}C)$		0.73	0.85	V
Instantaneous Reverse Current	I_R Note 1	$V_R=150V(T_a=25^{\circ}C)$		3.0	30	μA
		$V_R=150V(T_a=125^{\circ}C)$		5.0	15	mA

/Notes

1. /Short duration pulse test used to minimize self-heating effect.
2. / Unless otherwise noted, values for the parameters of a single chip







Note:


BR: Company Code

LV40150 Product Type

F: Package Code

CT: Internal Structure

****: Lot No. Code, code change with Lot No.



Note:

- 1

25 150

60 90sec;
- 2

255 5

5 0.5sec;
- 3

2 10

/sec.
- 1.Preheating:25~150

, Time:60~90sec.
- 2.Peak Temp.:255 5

, Duration:5 0.5sec.
3. Cooling Speed: 2~10

/sec.

270 5

10 1 sec.

Temp.:270±5℃

Time:10±1 sec

/ BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Bag 只/袋	Bags/Inner Box 袋/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Bag 袋	Inner Box 盒	Outer Box 箱
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

/ TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Tube 只/套管	Tubes/Inner Box 套管/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Tube 套管	Inner Box 盒	Outer Box 箱
TO-220/F	50	20	1,000	5	5,000	532×31.4×5.5	555×164×50	575×290×180