

TO-263

Ultrafast Recovery Diode in a TO-263 Plastic Package.

Silicon epitaxial process to produce ultrafast recovery diode with low reverse leakage current and high reliability.

For high frequency, high voltage, high current rectifier diode, freewheeling diode.



PIN1 Anode

PIN 2,4 Cathode

PIN 3 Anode






See Marking Instructions.


Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	600	V
RMS Voltage	V_{RMS}	420	V
DC Blocking Voltage	V_{DC}	600	V
Average Forward Current	I_F	2×8	A
Non Repetitive Peak Surge Current	I_{FSM}	125	A
Thermal Resistance Junction to Case	R_{JC}	2.5	/W
Junction and Storage Temperature Range	T_j, T_{stg}	-55~150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage	V_F	$I_F=8A(T_C=25^{\circ}C)$			1.8	V
		$I_F=8A(T_C=150^{\circ}C)$		1.05	1.3	V
		$I_F=16A(T_C=125^{\circ}C)$			2.0	V
		$I_F=16A(T_C=150^{\circ}C)$		1.28	1.6	V
Instantaneous Reverse Current ^(Note1)	I_R	$V_R=600V(T_a=25^{\circ}C)$			5	A
		$V_R=600V(T_a=150^{\circ}C)$		16	100	A
Reverse Recovery Time	t_{rr}	$I_F=0.5A \quad I_R=1.0A$ $I_{RR}=0.25A$			50	ns

/Notes:

1. /Short duration pulse test used to minimize self-heating effect.
2. / Unless otherwise noted, values for the parameters of a single chip






单位: mm

Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeter	
	Min	Max		Min	Max
A	4.30	4.70	E	9.00	9.40
E	2.00	2.40	e1	2.24	2.74
b	0.70	0.90	e2	4.88	5.28
b1	1.15	1.35	L1	15.00	16.00
b2	0.40	0.60	L2	2.24	2.94
C	1.20	1.40	L3	1.20	1.60
D	9.80	10.20			

TP-263



BR

MURB1660

CT:

Note:

BR: Company Code.


MURB1660 Product Type.

CT: Internal Structure

****: Lot No. Code, code change with Lot No.



Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1

25 150

60 90sec;
- 2

245±5

5±0.5sec;
- 3

2 10 /sec.
- 1.Preheating:25~150

, Time:60~90sec.
- 2.Peak Temp.:245±5

, Duration:5±0.5sec.
3. Cooling Speed: 2~10

/sec.

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
TO-263	800	1	800	5	4,000	13" ×24	360×360×50	385×257×392

/ TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Tube 只/套管	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
TO-263	126,856	1	126,856	5	634,280	13" ×24	360×360×50	385×257×392