

Rev.H May.-2019

50V~1000V 2.0A SMAF

Surface Mount General Purpose Silicon Rectifiers, Reverse Voltage: 50 to 1000V, Forward Current: 2.0A, SMAF package.


RoHS 2011/65/EU

Glass Passivated Chip Junction High efficiency Lead free in comply with EU R HS 2011/65/EU directives For surface mounted applications. Halogen free product.

General purpose.



PIN	DESCRIPTION
1	Cathode
2	Anode



See Marking Instructions.

Parameter	Symbol	Rating							Unit
		S2AF	S2BF	S2DF	S2GF	S2JF	S2KF	S2MF	
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current at $T_c = 125$	$I_{F AV}$	2.0							A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I_{FSM}	50							A
Typical Junction Capacitance ¹	C_j								

Note:

- 1 Measured at 1 MHz and applied reverse voltage of 4 V D.C
- 2 P.C.B. mounted with 2.0 X 2.0" (5 X 5 cm) copper pad areas.

Parameter	Symbol	Test condition	Rating	Unit
Maximum Instantaneous Forward Voltage	V_F	$I_F=2.0A$	1.1	V
Maximum DC Reverse Current at Maximum DC Blocking Voltage	I_R	$T_a=25$	5.0	uA
		$T_a=125$	100	

Rev.H May.-2019

Fig.1 Forward Current Derating Curve




Fig.2 Typical Instantaneous Reverse




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance






Fig.5 Maximum Non-Repetitive Peak Forward Surge Current




Rev.H May.-2019



UNIT	A	C	D	E	e	g	H _E	b
max	1.2	0.20	3.7	2.7	1.6	1.2	4.9	1.05
mm								
min	0.8	4.4	0.65	7°	0.9	0.12	3.3	2.4
max	47	193	41		47	7.9	146	106
mil								
min	24	173	36		25	1.7	130	94

Rev.H May.-2019



S2A

1 *


3 *

Note:

S2A Product Type Code

Lot No. Code The 1st * means:YM Code The last 3 * means:little Lot No
Code

Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1 150 180 60 90sec;
- 2 245±5 5±0.5sec;
- 3 2 10 /sec.

- 1.Preheating:150~180 , Time:60~90sec.
- 2.Peak Temp.:245±5 , Duration:5±0.5sec.
3. Cooling Speed: 2~10 /sec.

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box
SMAF	3000	5	15000	5	75000	7 ×11	185X180X105	390X385X205