

/ Revised record

A	2019-7-23	all	SMA-S-SS52_SS520-5A200V		
B	2021-3-16	2 4 7	V_F SS58 0.7 V_F SS58 0.85 5 50000 7 70000 340X340X40 350X350X230 336X336X40 380X335X366		

SS52~SS520
Rev. B Mar.-2021



DATA SHEET

Parameter	Symbol	Rating								Unit
		SS52	SS54	SS56	SS58	SS510	SS512	SS515	SS520	
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	20	40	60	80	100	120	150	200	V
Maximum RMS voltage	V_{RMS}	14	28	42	56	70	84	105	140	V
Maximum DC Blocking Voltage	V_{DC}	20	40	60	80	100	120	150	200	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	5.0								A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	I_{FSM}	120								A
Typical Junction Capacitance ¹⁾	C_j									

/ Electrical Characteristic Curve

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance




Fig.5 Maximum Non-Repetitive Peak






Fig.6 Typical Transient Thermal Impedance Forward Surge Current




/ Package Dimensions

SMA



Marking

Type number	Marking code
SS52	SS52
SS54	SS54
SS56	SS56
SS58	SS58
SS510	SS510
SS512	SS512
SS515	SS515
SS520	SS520




1

3

SS52

Lot No. Code The 1st means:YM Code The last 3 means:little Lot No
Code

() /



Note:

- | | | | |
|---|------------|-----------|---|
| 1 | 150 180 | 60 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245±5 | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | 2 10 /sec. | | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel /	Reels/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Reel	Inner Box	Outer Box